

## Basis Nappa Specifications

| Test   | Test Method                           | Measurement Unit        | Requirement                     |
|--|---------------------------------------|-------------------------|---------------------------------|
| Thickness  | DIN 53326                             | mm                      | 1.0 - 1.4                       |
| Mass per unit area                                       | DIN 53327                             | g/qm                    | 620 - 980                       |
| Tension test Tensile test Breaking elongation            | DIN 53328<br>Specimen 2<br>Specimen 2 | <b>N</b><br>%           | > 120<br>35 - 70                |
| Tear strength  | DIN 53329/A<br>DIN 53329/B            | N                       | > 25<br>> 20                    |
| Behaviour after 20,000 folds                             | DIN 53351                             |                         | No cracks at 6 times magnifying |
| Behaviour after ageing 1 period 10,000 folds             |                                       |                         | No cracks at 6 times magnifying |
| Water vapour permeability                                | DIN 53333                             | mg/qcm                  | 1.0                             |
| Rub fastness<br>Dry<br>Wet<br>Wet after storage in water | DIN 53339<br>evaluation<br>DIN 54002  | Class<br>Class<br>Class | 4-5<br>4-5<br>4-5               |
| Sweat  |                                       | Class                   | 4-5                             |
| Top coat adhesion  |                                       | N/cm                    | 3.5                             |
| High temperature light exposure                          | DIN 75202                             | Class blue scale        | 5.7                             |
| Flammability   | FMVSS 302                             | mm/min                  | < 100                           |
| Odour test   | VDA 270 C3                            | Class                   | < 3                             |
| VDA list   |                                       |                         | Keeping to the list             |

## What you should know about ordering leather

Due to the beautiful natural characteristics of leather, there may be some variation in shade and texture within a hide, and between hides. Although hides are free from excessive scars, there is always some evidence of their natural origin. Size will also vary between hides, but a typical hide is between 4.5-5.5m². Please contact us for sizes available.

Samples are a good guide to colour and finish, but you should bear in mind an exact match cannot be guaranteed.